



ROTARY ACTUATOR



	Moment of inertia	1-2
MCRA	$\varnothing 63$	1-4
MCRB	$\varnothing 16 \sim \varnothing 32$	1-8
MCRJ	$\varnothing 6, \varnothing 8$	1-12
F MCRQ	$\varnothing 12 \sim \varnothing 40$	1-14
MCRQ-S	$\varnothing 16 \sim \varnothing 25$	1-20
MRT*	$\varnothing 40 \sim \varnothing 80$ MRT / MRTF	1-22

F Fast delivery


Moment of inertia

ROTARY ACTUATOR



- The load will create inertial forces (kinetic energy) when moving the load with Rotary Actuator. In order to stop the moving load, it is necessary to use stopper or Shock Absorbers to absorb the kinetic energy of load.
- The moving load with actuator can be distinguished as following
 - Linear motion (air cylinder), Fig.(1)
 - Rotation motion (rotary actuator), Fig.(2)
- Calculate the kinetic energy by using the formula in FIG.

Linear motion




E : Kinetic energy
m : Load mass
V : Speed

$$E = \frac{1}{2} \cdot m \cdot V^2 \dots (1)$$

Fig. (1) Linear motion

Rotation motion



E : Kinetic energy
I : Moment of inertia ($= m \cdot r^2$)
 ω : Speed
m : Mass
r : Radius of rotation


$$E = \frac{1}{2} \cdot I \cdot \omega^2 = \frac{1}{2} \cdot m \cdot r^2 \cdot \omega^2 \dots (2)$$

Fig. (2) Rotation motion

- For linear motion, if the velocity V of formula (1) is constant, the kinetic energy E and mass m is proportional; The rotation motion, formula (2) shows even the angular velocity ω and mass m is constant, kinetic energy E will also proportional with r^2 . Therefore, even the mass is small but the rotation radius r is large, when the moment of Inertia $I = m \cdot r^2$ is large, kinetic energy E will becomes larger, it will cause bearing damage or other accidents.
- Therefore when there is a rotation motion, the product selection should be base on moment of inertia instead of mass.

Moment of inertia

- Moment of inertia shows, it is not easy to rotate the stationary object; the same which means it is difficult to stop the rotating object.
- Rotary Actuators in the allowable kinetic energy has its limitations, it can be calculated moment of inertia to calculate minimum rotation of moment of inertia described as following.



$$I = m \cdot r^2$$

m : Mass

r : Radius of rotation


Above figure represents the moment of inertia for the distance r from rotary shaft to mass m of the object.

The formula for moment of Inertia is not the same if the shapes of the object are different.

The following examples are the calculated on the basis of specific moment of inertia.

1. Thin shaft


Position of rotational axis: Perpendicular to the shaft through the shaft through the center of gravity.



$$I = m \cdot \frac{a^2}{12}$$

2. Thin rectangular plate

Position of rotational axis: Parallel to side b and through the center of gravity.



$$I = m \cdot \frac{a^2}{12}$$


Moment of inertia

ROTARY ACTUATOR




3. Thin rectangular plate (Including rectangular parallelepiped)

Position of rotational axis: Perpendicular to the plate through the center of gravity.




4. Round plate (Including column)

Position of rotational axis: Through the center axis.




5. Solid sphere

Position of rotational axis: Through the center of diameter.




6. Thin round plate

Position of rotational axis: Through the center of diameter.



7. Gear transmission



Use the following formula to calculate the rotation time

$$t \geq \sqrt{\frac{2 \cdot I \cdot \theta^2}{E}}$$

t : Rotation time (s)
E : Kinetic energy (J)
I : Moment of inertia (kg.m²)
θ : Rotation angle (rad)

The meaning of this formula is the critical rotation time for not cause damage of the cylinder. Therefore the rotation time must be set on or over the t seconds calculated in above formula.

After calculated the moment of inertia by load shape, use the following formula to calculate the kinetic energy of the load.

$$E = 1/2 \cdot I \cdot \omega^2$$

E : Kinetic energy (J)
I : Moment of inertia (kg.m²)
ω: Angle speed (rad/s)

Angle speed

$$\omega = 2\theta / t \dots (1)$$

$$\omega = \theta / t \dots (2)$$

t : Rotation time (s)
I : Moment of inertia (kg.m²)
θ : Rotation angle (rad)


However, when the rotation time for 90° becomes longer than 2 seconds, use formula (2).

Calculation example

Load form: Cuboid
Rotation angle θ: 180°
Rotation time t: 1 s/180°

Length of a part: 0.12 m
Length of b part: 0.06 m
Mass (m) : 0.1 kg

$$I = m \cdot \frac{a^2 + b^2}{12}$$



(Step 1) Find the angle speed ω.

$$\omega = \frac{2\theta}{t} = \frac{2}{1} \times \pi = 6.28 \text{ rad/s}$$

(Step 2) Find the moment of inertia I.

$$I = m \cdot \frac{a^2 + b^2}{12}$$

$$= 0.1 \times \frac{144 \times 10^{-4} + 36 \times 10^{-4}}{12}$$

$$= 1.5 \times 10^{-4} \text{ kg.m}^2$$


(Step 3) Find the kinetic energy E.

$$E = \frac{1}{2} \cdot I \cdot \omega^2 = \frac{1}{2} \times 1.5 \times 10^{-4} \times 6.28^2$$

$$= 0.002958 \text{ J}$$



Symbol



Features


- Compact body.
- Functional design with clean appearance.
- Simple mounting of sensors.
- Magnetic as standard.

Specification


Model	MCRA		
Acting type	Double acting		
Tube I.D. (mm)	$\varnothing 63$		
Port size	Rc1/8		
Medium	Air		
Operating pressure range	0.1~1MPa		
Proof pressure	1.5MPa		
Ambient temperature	-5~+60°C (No freezing)		
Acting angle tolerance	0~+4°		
Lubrication	Not required		
Cushion	Air cushion		
Allowable kinetic energy	1.5J (Air cushion)		
Sensor switch (*)	RCB, RCE, RCE1, RDEP		
Weight (kg)	90°	180°	LB
	2.7	3.1	0.4

* RCB, RCE, RCE1, RDEP specification, please refer to page 5-4, 6, 9.


Order example




Shaft loading



Torque diagram







Material

No.	Part name	Material	Q'y	Repair kits (inclusion)
1	Body	Aluminum alloy	1	
2	Shaft	Carbon steel	1	
3	Rack	Carbon steel	1	
4	Cover	Aluminum alloy	2	
5	Slider	Plastic	2	
6	Bearing retainer	Aluminum alloy	1	
7	Piston #1	Aluminum alloy	2	
8	Piston #2	Aluminum alloy	2	
9	Screw #1	Carbon steel	2	
10	Screw #2	SCM	2	
11	Bolt	SCM	8	
12	Screw	SCM	4	
13	Spring pin	Spring steel	4	
14	Spring washer	SCM	8	
15	Bearing	Bearing steel	2	
16	Piston packing	NBR	2	●



No.	Part name	Material	Q'y	Repair kits (inclusion)
17	Magnet ring	Magnet material	2	
18	Gasket	NBR	2	●
19	O-ring	NBR	2	●
20	Cushion packing	NBR	2	
21	Needle valve	Copper	2	
22	Needle valve gasket	NBR	2	●
23	Needle valve washer	Aluminum alloy	2	
24	Parallel key	Carbor steel	1	


Order example of repair kits

Tube I.D.	Repair kits
ø63	PS-MCRA-63




Installation of sensor switch





Order example

MCRB – 20R – FR – □



Features


- Twin rack and pinion fitted as standard.
- Can be adjusted between 0 and 190 degrees.
- Simple mounting of sensors.
- Magnetic as standard.

Specification


Model	MCRB			
Acting type	Double acting			
Tube I.D. (mm)	16	20	25	32
Port size	Rc1/8			
Medium	Air			
Operating pressure range	0.1~1MPa			
Proof pressure	1.5MPa			
Ambient temperature	-5~+60°C (No freezing)			
Lubrication	Not required			
Cushion	NBR spacer			
Allowable kinetic energy	Cushion pad	0.007J	0.040J	0.081J
	Cushion	0.039J	0.116J	0.294J
				1.6J
Stable rotation time regulation range	0.2~1.0 s/90°			
Sensor switch (*)	RCD			
Weight (kg)	0.7	1.16	1.57	3.07

* RCD specification, please refer to page 5-5.


Symbol




Action profile



Installation of sensor switch



Torque diagram







Theoretic force


Unit: N·m

Type		MCRB			
Tube I.D.		16	20	25	32
Operating pressure (MPa)	0.1	0.26	0.5	0.91	1.88
	0.2	0.52	1	1.81	3.78
	0.3	0.78	1.5	2.72	5.66
	0.4	1.04	2.01	3.62	7.56
	0.5	1.31	2.51	4.55	9.44
	0.6	1.57	3	5.45	11.32
	0.7	1.83	3.5	6.36	13.23

Allowable load

Set the load and moment to be applied to the table within the allowable values shown in the table below.
(Values outsize of limitations will cause excessive play, deteriorate accuracy, and shorten service life.)

Pictures	Tube I.D.	Allowable radial load (N)		Allowable thrust load (N) (a) (b)	Allowable moment (N.m)
		(a)	(b)		
	16	78	74	78	2.4
	20	196	197	363	5.3
	25	314	296	451	9.7
	32	390	493	708	18



Material


No.	Part name	Material	Q'y	Repair kits (inclusion)
1	Body	Aluminum alloy	1	
2	Cover	Aluminum alloy	1	
3	End cover	Aluminum alloy	1	
4	Piston	Stainless steel	2	
5	Pinion	SCM	1	
6	Bearing retainer	Aluminum alloy	1	
7	Table	Aluminum alloy	1	
8	Seal nut	Stainless steel	2	
9	Shock absorber	Stainless steel	2	
10	Cushion pad	NBR	2	●
11	Plate	Aluminum alloy	1	
12	Packing	NBR	1	●
13	Gasket	NBR	2	●
14	Fixed	Copper	2	
15	Ball bearing	Bearing steel	1	
16	Ball bearing	Bearing steel	1	
17	Snap ring	Spring steel	1	
18	Screw	SCM	8	
19	Screw	SCM	12	
20	Magnet	Magnet material	2	
21	Wearing	Teflon	4	
22	Piston packing	NBR	4	●
23	O-ring	NBR	2	●
24	O-ring	NBR	2	●
25	O-ring	NBR	2	●

Order example of repair kits

Tube I.D.	Repair kits
ø16	PS-MCRB-16
ø20	PS-MCRB-20
ø25	PS-MCRB-25
ø32	PS-MCRB-32


MCRB Dimensions $\varnothing 16 \sim \varnothing 32$

ROTARY ACTUATOR



MCRB-*R

Shock absorber



Code Tubr I.D.	A	B	C	D	E	F	G	H	H1	I	J	K	L	M	N	O	P
16	108	58	47	62	38	15	38	50	48	M5×7dp,P.C.D38	33	8	M5×8dp	14	26	15.5	Rc1/8
20	128	68	55	78	47	15	46	62.5	60	M6×7dp,P.C.D46	38	10	M6×8dp	17	27	18.5	Rc1/8
25	135.5	77	58.5	84	55	15.5	48	67	65	M6×9dp,P.C.D48	41.5	10	M6×8dp	17	37	20	Rc1/8
32	170	94	69.5	106	68	20	55	85	83	M8×10dp,P.C.D55	49.5	12.5	M8×8.5dp	20	47	24	Rc1/8


Code Tubr I.D.	Q	S1	S2	T	U	V	W1
16	8 ^{+0.03} ₋₀ (wide)×3.3dp	6	17 (H7)×2.5dp	24 (H7)×3dp	2-ø6.8 thru, ø11×6.5dp, M8×12dp(sink)	M3×4dp	M10×1.0
20	10 ^{+0.03} ₋₀ (wide)×3.5dp	10	22 (H7)×2.5dp	32 (H7)×3dp	2-ø8.6 thru, ø14×8.5dp, M10×15dp(sink)	M4×6dp	M12×1.0
25	12 ^{+0.03} ₋₀ (wide)×4dp	13	22 (H7)×3dp	32 (H7)×3.7dp	2-ø8.6 thru, ø14×8.5dp, M10×15dp(sink)	M4×5dp	M14×1.5
32	12 ^{+0.03} ₋₀ (wide)×5dp	13	26 (H7)×3dp	35 (H7)×4.7dp	2-ø10.5 thru, ø18×10.5dp, M12×18dp(sink)	M5×5dp	M20×1.5

Code Tubr I.D.	W3	X1	X2	Y1	Y2
16	26	7	17	FK-1008L-S	24
20	32	8	19	FK-1210L-S	36.5
25	37	8	22	FK-1412L-S	41
32	47	12	30	FK-2016L-S	55

Flange rod type

$\varnothing 16$

$\varnothing 20 \sim \varnothing 32$




Code Tubr I.D.	A	E	J	K	L	N
16	64.5	31.5	17.5	-	-	-
20	78	40	23	16	9.2	8
25	81.5	40	23	20	11.2	10
32	109.5	60	40	20	13.2	12

* Other dimensions are the same as standard type.

MCRJ series

MINI-ROTARY ACTUATOR



Features

- Rack and pinion type / with external stoppers.
- Mounting from 3 directions.
- Piping and wiring are same directions.
- More compact.

Specification

Model	MCRJ	
Tube I.D. (mm)	6	8
Port size	M3 × 0.5	
Rotation	90°, 180°	
Medium	Air (Non-lube)	
Operating pressure range	0.15~0.7 MPa	
Ambient temperature	0~+60°C	
Angle adjustment range	Each rotation end ±5°	
Weight (g)	90° 48	180° 54
Sensor switch	RT: Reed switch, RTN: NPN, RTP: PNP	

* RT specification, please refer to page 5-14.

Order example

MCRJ – 6 – 90

MODEL TUBE I.D.

ROTARY ANGLE	
Code	Rotary angle
90	90°
180	180°

Auto switch type

RT × 1

NUMBER of
AUTO SWITCH


AUTO SWITCH TYPE

perpendicular	in-line	style
RTV	RT	Reed switch
RTNV	RTN	NPN
RTPV	RTP	PNP

Effective torque


Model	Operating pressure (MPa)						
	0.15	0.2	0.3	0.4	0.5	0.6	0.7
MCRJ-6	0.013	0.017	0.026	0.034	0.042	0.05	0.059
MCRJ-8	0.029	0.038	0.057	0.076	0.095	0.11	0.13

Note. Effective torque values are representative values. They are not guaranteed values. Use them only as a guide.




MCRJ Dimensions ø6, ø8

MINI-ROTARY ACTUATOR




Code Tubr I.D.	Rotation angle	A	B	C	CC	D	E	EA	EB	EH	F	H	I	IA	IB	II	J	JA	JB	JJ	
6	90°	19.5	43	21.5		5.5	3.5	5g6	33.8	5.6	6.5	17.1	14.5	20	5	7	M4 × 0.7	30	5.8	3.5	M4 × 0.7
	180°		54	27																	
8	90°	23.5	48	24		7.5	4.5	6g6	35.8	5.6	7.5	21.1	15.5	22	6	8.5	M5 × 0.8	35	7.5	4.5	M5 × 0.8
	180°		61	30.5																	

Code Tubr I.D.	Rotation angle	K	KA	KK	M	TA	W
6	90°	32.4	9.5	28	4.5	3.4	13.5
	180°	43.4					
8	90°	37.4	12.5	32	5.5	5.9	16.5
	180°	50.4					




Symbol



Order example


MCRQ – 20R – □ – □




ANGLE ADJUSTER
 A: With adjusting bolt
 R: With shock absorber
 * ø12 without shock absorber.

PIPING TYPE(*)

Blank: End port



E: Front port



* ø12 only option.

* Piping port cannot be changed after delivery.

PORT THREAD

Blank: M5×0.8
 (for ø12, ø16)

Blank: Rc thread

G: G thread

NPT: NPT thread

(for ø20~ø40)

Features

- Centering boss and locating hole for accurate positioning.
- Operating range of table is 0°~190° by angle adjusting screw.
- Compact design using double rack and single pinion.
- Hollow shaft standard for wiring and piping.
- Possible to fit shock absorbers as stops.
- Ease of mounting with integral table.
- Magnetic as standard.

Specification

Model	MCRQ					
Acting type	Double acting					
Tube I.D. (mm)	12	16	20	25	32	40
Port size	M5×0.8		Rc1/8			
Medium	Air					
Max. operating pressure	adjusting bolt shock absorber	0.7MPa —	1 MPa 0.6 MPa (*1)			
Min. operating pressure	0.1 MPa (*2)					
Ambient temperature	0~+60°C (No freezing)					
Cushion	adjusting bolt shock absorber	—	Rubber bumper Shock absorber			
Angle adjustment range	0° to 190°(max.) (*3)					
Sensor switch (*4)	RDF(V), RNF(V): NPN, RPF(V): PNP					
Weight (kg)	adjusting bolt shock absorber	0.25 —	0.60 0.61	1.24 1.31	2.10 2.12	4.18 4.19
Minimum rotation that will not allow decrease of energy absorption ability	—	72°	58°	69°	77°	82°

*1. The maximum operating pressure of the actuator is restricted by the maximum allowable thrust of the shock absorber.

*2. No-load conditions.

*3. Be careful if the rotation angle of a type with internal shock absorber is set below the value in the table below, the piston stroke will be smaller than the shock absorber's effective stroke, resulting in decreased energy absorption ability.


*4. RDF specification, please refer to page 5-10.

Allowable kinetic energy and rotation time adjustment range

Model	Allowable kinetic energy (J)		Rotation time adjustment range for stable operation(s/90°)		
	Adjustment bolt	Internal shock adsorber	Adjustment bolt	Internal shock adsorber	
MCRQ-12	0.006	—	0.2 to 1.0	—	
MCRQ-16	0.007	0.039		0.2 to 0.7	
MCRQ-20	0.048	0.116	0.2 to 2.0		
MCRQ-25	0.081	0.294	0.2 to 1.0		
MCRQ-32	0.32	1.6		0.2 to 2.5	
MCRQ-40	0.53	2.9			

* Be careful if a type with internal absorber is used below the minimum speed, the energy absorption ability will decrease drastically.

Torque diagram






Theoretic force

Unit: N·m



Type	MCRQ					
Tube I.D.	12	16	20	25	32	40
Operating pressure (MPa)	0.1	0.1	0.26	0.5	0.91	1.88
	0.2	0.21	0.52	1	1.81	3.78
	0.3	0.31	0.78	1.5	2.72	5.66
	0.4	0.41	1.04	2.01	3.62	7.56
	0.5	0.52	1.31	2.51	4.55	9.44
	0.6	0.63	1.57	3	5.45	11.32
	0.7	0.73	1.83	3.5	6.36	13.23
						26.4

Allowable load


Set the load and moment to be applied to the table within the allowable values shown in the table below.
 (Values outside of limitations will cause excessive play, deteriorate accuracy, and shorten service life.)

Pictures	Tube I.D.	Allowable radial load (N)	Allowable thrust load (N)		Allowable moment (N.m)		
			(a)	(b)			
			12	71	71	1.5	
			(a)	(b)			
							
							
12	54	71	71		1.5		
16	78	74	78		2.4		
20	196	197	363		5.3		
25	314	296	451		9.7		
32	390	493	708		18		
40	543	740	1009		25		


ø16~ø32



ø40



ø12



Material

No.	Part name	Material	Tube I.D. & Q'y				Repair kits (inclusion)
			12	16	20~32	40	
1	Body	Aluminum alloy		1			
2	Cover	Aluminum alloy	2	1			
3	End cover	Aluminum alloy	2	1			
4	Pinion	SCM		1			
5	Bearing retainer	Aluminum alloy		1			
6	Table	Aluminum alloy		1			
7	Piston	Stainless steel		2			
8	Rolling bearing	Bearing steel		1			
9	Rolling bearing	Bearing steel		1			
10	Snap ring	Spring steel	-	1		-	
11	Seal nut	Carbon steel		2			
12	O-ring	NBR	4	2	4		●
13	Shock absorber	Stainless steel *1		2			
14	Cushion pad	NBR		2			
15	Magnet	Magnet material	4		2		
16	Seal washer	*2		2			●
17	Fixed	Copper	-	4	2	-	
18	Piston packing	NBR	1	-	2	-	●
19	O-ring	NBR	-	4	2	-	●
20	Wear ring	Complex resin		4			

*1. ø40: Carbon steel

*2. ø12~ø32: NBR+Stainless steel; ø40: NBR

No.	Part name	Material	Tube I.D. & Q'y				Repair kits (inclusion)
			12	16	20~32	40	
21	Piston Seal	NBR		4			●
22	Stop chunk	Aluminum alloy	-	2		-	
23	Pin *3	SCM		1			
24	Plate	Aluminum alloy	1		-		
25	Plug	Copper		-		1	
26	Plug washer	PET		-		1	
27	Piston retainer	Aluminum alloy		-	2		
28	Piston snap ring	Spring steel		-	2		
29	Plug	Carbon steel		-	2		

*3. ø20~ø40: Key

Order example of repair kits

Tube I.D.	Repair kits
ø12	PS-MCRQ-12
ø16	PS-MCRQ-16
ø20	PS-MCRQ-20
ø25	PS-MCRQ-25
ø32	PS-MCRQ-32
ø40	PS-MCRQ-40

MCRQ Dimensions ø12

ROTARY ACTUATOR



Rotary Actuator






Clamp Cylinder


Gripper

Electric Actuator

Auxiliary Equipment



Hydraulic Cylinder





MCRQ-16~25R

With shock absorber



Unit: mm

Code Tubr I.D.	A	AA	B	BB	C	D	DA	DD	E	F	G	H	HH	I	J	K	L	LA	LB	LC	MA	MM	N
16	34	14	4.5	7	8	13	12	M8×1.25	6	15H9	9.5	47	3H9×3.5	60	27	26	92	20H9	45h9	46h9	8	M5×0.8	37
20	40	17	6.5	8	10	17	15	M10×1.5	10	22H9	12	57	4H9×4.5	84	37	32	127	32H9	65h9	67h9	8	M6×1	54
25	46	22	7.5	8	12	20	18	M12×1.75	13	26H9	15.5	66	5H9×5.5	100	50	37	152	35H9	75h9	77h9	8	M8×1.25	63

Code Tubr I.D.	O	P	PP	QA	QB	QQ	R	RP	RR	S	T	TT	UA	UB	UU	W	X	XA	XX	Y	YA	YY	ZX
16	15.5	4	FK-1008L-S	8	32	M5×0.8	29	29	31	M10×1.0	5.5	M5×0.8	11	6.5	6.8	50	15	3.5	3H9	27	3.5	3H9	19
20	19.5	4.5	FK-1008L-S	10	48	M6×1.0	33	36	23	M10×1.0	4.5	Rc1/8	14	8.5	8.6	70	23	4.5	4H9	39	4.5	4H9	28
25	22	5	FK-1412L-S	12	55	M8×1.25	37.5	33	28	M14×1.5	7.5	Rc1/8	18	10.5	10.5	80	26.5	5.5	5H9	45	5.5	5H9	33





MCRQ Dimensions Ø32, Ø40

ROTARY ACTUATOR





MCRQ-32R, 40R

With shock absorber



MCRQ-40




Unit: mm

Code Tubr I.D.	A	AA	B	BB	C	D	DA	DD	E	F	G	H	HH	I	J	K	L	LA	LB	LC	M	MA
32	59	30	12	Bolt width 12	14.5	27	18	M12×1.75	13	24H9	17	86	6H9×4.5	130	66	47	189	56H9	98h9	100h9	102	10
40	74	36	15	Bolt width 21	16.5	32	25	M16×2.0	24	32H9	24	106	8H9×6.5	150	80	60	240	64H9	116h9	118h9	120	13

Code Tubr I.D.	MM	N	O	P	PP	QA	QB	QQ	R	RP	RR	S	T	TT	U	UA	UB	UU	W	X	XA
32	M8×1.25	85	27.5	6	FK-2016L-S	14.5	77	M10×1.5	50.5	46	34	M20×1.5	10.5	Rc1/8	42	18	10.5	10.5	95	37.5	6.5
40	M12×1.75	100	37	9	FK-2725L-S	16.5	90	M12×1.75	65.5	68	45	M27×1.5	7	Rc1/8	57	20	12.5	14.2	113	44	8.5

Code Tubr I.D.	XX	Y	YA	YY	ZX
32	6H9	59	4.5	6H9	49
40	8H9	69	4.5	8H9	54



Order example

MCRQ - S - 20 - 1 - G			
MODEL	EXTERNAL SHOCK ABSORBER	TUBE I.D.	PORT THREAD
			Blank: M5×0.8 (for Ø16) Blank: Rc thread G: G thread NPT: NPT thread (for Ø20, Ø25)
CONNECTING PORT POSITION AND ROTATION			
1	180°	2	90°
Connecting port		Connecting port	

Auto switch type

RDF × 1		
NUMBER of AUTO SWITCH		
AUTO SWITCH TYPE		
perpendicular	in-line	style
RDFV	RDF	Solid state
RNFV	RNF	NPN
RPFV	RPF	PNP

Notice for shock absorber

- The threaded orifices shown below are not connecting ports. Never remove the plugs as this will cause malfunction.
- Never rotate the bottom screw of the shock absorber. (It is not an adjustment screw.) This may cause oil leakage.

Features

- 4 to 10 times more allowable kinetic energy (compared with internal shock absorber type)

- Total length shortened

Longitudinal mounting space is reduced because there is no protrusion from adjustment bolts or internal shock absorbers.

Specification

Model	MCRQ-S		
Acting type	Double acting		
Tube I.D. (mm)	16	20	25
Port size	M5×0.8		
Rotation	90°, 180°		
Medium	Air (Non-lube)		
Max. operating pressure	1 MPa (*1)		
Min. operating pressure	0.2 MPa		
Ambient temperature	0~+60°C (No freezing)		
Allowable kinetic energy (J)	0.231	1.21	1.82
Rotation time adjustment range (s/90°)	0.2~1.0 (*2)		
Cushion	Shock absorber		
Shock absorber type	MDSC-1008-3N	MDSC-1008-3N	MDSC-1412-3N
Angle adjustment range	Each rotation end ± 3°		
Weight (kg)	90°	1.67	1.55
	180°	0.64	1.48
Sensor switch (*3)	RDF(V), RNF(V): NPN, RPF(V): PNP		


*1. The maximum operating pressure of the actuator is restricted by the maximum allowable thrust of the shock absorber.

*2. For stable operation the time required for the rotary table to reach the rotation end after deceleration differs depending on the operating conditions (inertial moment of the load, rotation speed, and operating pressure), however, approximately 0.2 to 2 seconds are required.

*3. RDF specification, please refer to page 5-10.



Range of shock absorber operates

Model	Adjustment angle per rotation of angle adjustment screw	Range of angle the shock absorber operates (single side)
MCRQ-S-15	1.5°	12°
MCRQ-S-20	1.1°	9°
MCRQ-S-25	1.3°	11°





MCRQ-S Dimensions Ø16, Ø20, Ø25

ROTARY ACTUATOR


In the inertial moment and rotation time


Code Tubr I.D.	PP
16	MDSC-1008-3N
20	MDSC-1008-3N
25	MDSC-1412-3N



PIN hole size

Code Tubr I.D.	HH	ZX
16	3H9×3.5	19
20	4H9×4.5	28
25	5H9×5.5	33

Unit: mm

Code Tubr I.D.	A	B	C	D	DA	DD	E	F	G	H	I	J	K	L	LA	LB	LC	M	MA	MB	MC
16	34	4.5	8	13	12	M8×1.25	6	15H9	9.5	47	99.8	80.6	29	92	20H9	45h9	46h9	55.5	11	6.5	60
20	40	6.5	10	17	15	M10×1.5	10	22H9	12	57	119.3	110	33	127	32H9	65h9	67h9	59	14	8.5	84
25	46	7.5	12	20	18	M12×1.75	13	26H9	15.5	66	154.8	130	37.5	152	35H9	75h9	77h9	83.3	18	10.5	100


Code Tubr I.D.	MM	N	NB	NC	O	OA	P	QA	QB	QQ	R	S	SS	T	TT	U	U2	V	X	XA	XX	Z
16	6.8	37	6	12.5	20	15.6	46.1	8	32	M5×0.8	33	4	45.4	50	M5×0.8	11.5	0.3	7.5	15	3.5	3H9	44.3
20	8.6	54	8	16.5	27	21.5	60.9	10	48	M6×1	46	4.5	61.8	70	Rc1/8	13.5	0.5	9	23	4.5	4H9	60.3
25	10.5	63	8.5	19.5	32	28	76.7	12	55	M8×1.25	54.5	5	73.3	80	Rc1/8	18	0.5	11	26.5	5.5	5H9	71.5



MRTH Male pivot gear (standard type)

MRTH-D Male pivot gear (double end rod type)

MRTF Female pivot gear



Features

- Hard anodised aluminium body is standard.
- Clean lines with high functionality.
- Carbon steel rack and pinion with low backlash.
- Simple adjustment of rotary movement.
- Magnetic as standard.


Specification

Model	MRTF, MRTH, MRTH-D			
Tube I.D. (mm)	40	63	80	
Standard rotation (mm)	$90\pm 5^\circ, 180\pm 5^\circ$			
Initial position of slot (mm)	See dimensional feature			
Medium	Filtered air with or without lubrication			
Operating pressure range	0.13~0.7 MPa			
Ambient temperature	-5~+60°C (No freezing)			
Max. allowable axial thrust (kg)	10	12	20	
Max. allowable kinetic energy	90° 180°	0.266J 0.58J	0.675J 1.54J	1.34J 3.03J
Max. allowable radial trust (Fr)	514.5 N	725.2 N	896.7 N	
Sensor switch (*)	LN01A	LN02A	LN03A	


* LN**A specification, please refer to page 5-15.

Order example

MRTH - 40 - 90 - D



Max. allowable radial trust



Cylinder weight

Unit: kg


Tube I.D.	MRTH		MRTH-D		MRTF		Sensor switch	
	90°	180°	90°	180°	90°	180°		
40	3.00	3.10	3.05	3.15	2.84	2.94	0.065	
63	5.40	5.80	5.55	5.95	5.07	5.47	0.066	
80	9.75	10.30	9.99	10.54	9.19	9.74	0.086	

MRTH / MRTF Capacity Ø40~Ø80

ROTARY ACTUATOR



Compressed air consumption for a complete cycle



Unit: L/cycle

Model	Rotation	Operating pressure (MPa)									
		0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
MRTH40	90°	0.1571	0.2352	0.3133	0.3915	0.4696	0.5477	0.6259	0.7040	0.7821	0.8603
MRTF40	180°	0.3141	0.4704	0.6267	0.7829	0.9392	1.0955	1.2517	1.4080	1.5643	1.7205
MRTH63	90°	0.4383	0.6564	0.8744	1.0925	1.3105	1.5286	1.7466	1.9647	2.1828	2.4008
MRTF63	180°	0.8766	1.3127	1.7488	2.1850	2.6211	3.0572	3.4933	3.9294	4.3655	4.8016
MRTH80	90°	0.8480	1.2698	1.6917	2.1135	2.5354	2.9572	3.3791	3.8009	4.2228	4.6447
MRTF80	180°	1.6959	2.5396	3.3834	4.2271	5.0708	5.9145	6.7582	7.6019	8.4456	9.2893


Model	MRTH, MRTF		
Tube I.D.(mm)	40	63	80
Constant K	0.3491	0.3927	0.4712

The method of calculation (Compressed air consumption)

$$Q = 2 \times K \times A \times n \times Dg \times \frac{P+0.101}{0.101} \times 10^{-6}$$

- Q:** Compressed air consumption (L/cycle)
- A:** Piston area (mm²)
- Dg:** Rotation
- P:** Air pressure (MPa)
- K:** Constant
- n:** Cycle of operation (cycle/min)

Output torque table




MRTH / MRTF Inside structure & Parts list



ROTARY ACTUATOR

How to order the seal kit




Tube I.D.	Seal kit
40	MRTHSK40 - Including No.22,23,24,25,26,27
63	MRTHSK63 - Including No.22,23,24,25,26,27
80	MRTHSK80 - Including No.22,23,24,25,26,27

Tube I.D.	Seal kit
40	MRTFSK40 - Including No.22,23,24,25,26,27
63	MRTFSK63 - Including No.22,23,24,25,26,27
80	MRTFSK80 - Including No.22,23,24,25,26,27

MRTH


MRTH-D



Parts list

No.	Part name	Q'y	No.	Part name	Q'y	No.	Part name	Q'y
1	End cap	2	10	End cover	1	19	Hexagon socket head screw	8
2	Rack	1	11	Cushion needle	2	20	Magnet	2
3	Piston	2	12	Washer	2	21	Ball bearing	2
4	Magnet holder	2	13	Tie bolt	8	22	Piston packing	2
5	Piston nut	2	14	Adjusting screw	1	23	Cylinder gasket	2
6	Cylinder tube	2	15	Adjusting screw	1	24	Cushion packing	2
7	Housing	1	16	Lock nut	2	25	Needle gasket	2
8	Pinion shaft	1	17	Stopper pin	1	26	Piston gasket	2
9	End cover	1	18	Set screw	1	27	Rod packing	1

MRTF



Parts list


No.	Part name	Q'y	No.	Part name	Q'y	No.	Part name	Q'y
1	End cap	2	10	End cover	1	19	Hexagon socket head screw	8
2	Rack	1	11	Cushion needle	2	20	Magnet	2
3	Piston	2	12	Washer	2	21	Ball bearing	2
4	Magnet holder	2	13	Tie bolt	8	22	Piston packing	2
5	Piston nut	2	14	Adjusting screw	1	23	Cylinder gasket	2
6	Cylinder tube	2	15	Adjusting screw	1	24	Cushion packing	2
7	Housing	1	16	Lock nut	2	25	Needle gasket	2
8	Pinion shaft	1	17	Stopper pin	1	26	Piston gasket	2
9	End cover	1	18	Set screw	1	27	Rod packing	2

MRTH / MRTF Dimensions Ø40~Ø80


ROTARY ACTUATOR



MRTF Angle of rotation 90°




Angle of rotation 180°







Model	A		C	D	E	F	G	H	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Z
	90°	180°																						
MRTF-40	263	326	81	75	72	8	65	53	37.5	93	27.5	60	38	15	25	14	30	M6	5	16.5	35	4	G1/4 M6	
MRTF-63	306	377	95	90	82	10	75	75	42.5	110	30	70	56.5	16	30	19	32	M8	6	22	45	5	G3/8 M8	
MRTF-80	343	428	119	105	96	12	95	95	51.5	135	36	82	72	19	35	24	38	M10	6	27.5	45	6	G3/8 M10	

MRTH Angle of rotation 90°



Angle of rotation 180°




Model	A		C	D	E	F	G	H	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Z
	90°	180°																						
MRTH-40	263	326	112	75	72	8	65	53	37.5	93	27.5	60	38	M5	30	16	25	M6	5	18	35	4	G1/4 M6	
MRTH-63	306	377	138	90	82	10	75	75	42.5	110	30	70	56.5	M8	42	24	36	M8	8	27	45	5	G3/8 M8	
MRTH-80	343	428	170	105	96	12	95	95	51.5	135	36	82	72	M8	50	28	45	M10	8	31	45	6	G3/8 M10	

MRTH / MRTF Dimensions Ø40~Ø80







ROTARY ACTUATOR

MRTH-D Angle of rotation 90°




Angle of rotation 180°




Model	A		B	D	E	F	G	H	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Z
	90°	180°																						
MRTH-40-D	263	326	143	75	72	8	65	53	37.5	93	27.5	60	38	M5	30	16	25	M6	5	18	35	4	G1/4	M6
MRTH-63-D	306	377	181	90	82	10	75	75	42.5	110	30	70	56.5	M8	42	24	36	M8	8	27	45	5	G3/8	M8
MRTH-80-D	343	428	221	105	96	12	95	95	51.5	135	36	82	72	M8	50	28	45	M10	8	31	45	5	G3/8	M10

Mounting type

MRTF




Bottom mounting




Top mounting

MRTH




Bottom mounting




Top mounting

Rotating direction and adjustable angle



MRTF





MRTH



MRTH-D



MRTF



Tube I.D.	Sensor switch	A	B	C	D	E
40	LN01A	29	32	32	M4×8L	M4
63	LN02A	40	43	32	M4×10L	M4
80	LN03A	49.5	52	32	M4×12L	M4

MEMO

NOTE

